

MICHELIN ANAKEE 2

ADVENTURE TOURING

Exceptional mileage compared to competing tires

- ▶ 29% longer tread life than its closest competitors*, with no compromise in wet grip (radial sizes only)

Excellent all-weather performance

- ▶ Versatile tread design with deep channels for water evacuation
- ▶ Silica-charged rubber compound

Radial or bias to fit most adventure touring bikes

- ▶ Excellent tire for bikes like the BMW GS and Suzuki V-Strom
- ▶ Also great for older models that accept bias tires

*Compared with Bridgestone Trail Wing and Metzeler Tourance EXP. Test conducted by CERM (Centre d'Essais Routiers Mécaniques) in 2008 using radial sizes 110/80 R 19 and 150/70 R 17.



Size	Load index & Speed rating	Michelin Tube	Overall width				Overall diameter				Max load ¹		Tread depth ²		Preferred rim width (compatible rims) in
			Static mm	In Use in	Static mm	In Use in	Static mm	In Use in	kg	lbs	mm	32nds			
ANAKEE® 2 FRONT BIAS															
90/90-21	54 S	TL or 21MDR	90	3.54	99	3.90	695	27.36	713	28.07	212	467	5	6	2.15 (1.85 or 2.50)
90/90-21	54 H	TL or 21MDR	90	3.54	99	3.90	695	27.36	713	28.07	212	467	5	6	2.15 (1.85 or 2.50)
90/90-21	54 V	TL or 21MDR	90	3.54	99	3.90	695	27.36	713	28.07	212	467	5	6	2.15 (1.85 or 2.50)
100/90-19	57 H	TL or 19MF	101	3.98	111	4.37	663	26.10	685	26.97	230	507	5	6	2.50 (2.15 or 2.75)
ANAKEE® 2 REAR BIAS															
120/90-17	64 S	TL or 17MH	119	4.69	131	5.16	648	25.51	664	26.14	280	617	7	9	2.75 (2.15 to 3.00)
ANAKEE® 2 FRONT RADIAL															
110/80R19	59 H	TL or 19MF	109	4.29	120	4.72	659	25.94	681	26.81	243	536	5	6	2.50
110/80R19	59 V	TL or 19MF	109	4.29	120	4.72	659	25.94	681	26.81	243	536	5	6	2.50
ANAKEE® 2 REAR RADIAL															
130/80R17	65 S	TL or 17MH	129	5.08	142	5.59	640	25.20	654	25.75	290	639	8	10	3.00
130/80R17	65 H	TL or 17MH	129	5.08	142	5.59	640	25.20	654	25.75	290	639	8	10	3.00
140/80R17	69 H	TL or 17MI	142	5.59	156	6.14	656	25.83	682	26.85	325	717	8	10	3.50
150/70R17	69 H	TL or 17MI	149	5.87	164	6.46	642	25.28	656	25.83	325	717	8	10	4.25
150/70R17	69 V	TL or 17MI	149	5.87	164	6.46	642	25.28	656	25.83	325	717	8	10	4.25

MICHELIN M62 GAZELLE

URBAN / UTILITY

Great durability and long tread life

- ▶ Reinforced casing for high-stress loads
- ▶ Deep tread pattern for long wear

Resistant to tread cuts, punctures, and casing damage

- ▶ Tread plies overlap to strengthen tires and resist punctures

Comfortable ride

- ▶ Flexible sidewall provides excellent shock absorption

Size	Load index & Speed rating	Michelin Tube	Overall width				Overall diameter				Max load ¹		Tread depth ²		Preferred rim width (compatible rims) in
			Static mm	In Use in	Static mm	In Use in	Static mm	In Use in	kg	lbs	mm	32nds			
M62 GAZELLE™ FRONT/REAR															
2.25-17	38 P	None avail.	60	2.36	66	2.60	556	21.89	568	22.36	132	291	4	5	1.50 (1.20 to 1.60)
2.50-17	43 P	None avail.	64	2.52	70	2.76	568	22.36	580	22.83	155	342	5	6	1.50 (1.35 or 1.60)
2.75-17	47 P	None avail.	75	2.95	81	3.19	588	23.15	600	23.62	175	386			1.85 (1.50 or 1.60)
2.75-18	48 P	None avail.	75	2.95	81	3.19	613	24.13	625	24.61	180	397			1.85 (1.50 or 1.60)
M62 GAZELLE™ REAR															
3.00-17	50 P	None avail.	80	3.15	86	3.39	602	23.70	614	24.17	190	419	6	7	1.85 (1.60 or 2.15)
3.00-18	52 P	None avail.	80	3.15	86	3.39	627	24.69	639	25.16	200	441			1.85 (1.60 or 2.15)

¹Refer to the motorcycle owner's manual for the vehicle's load capacity. Michelin recommends the tire pressures quoted by the vehicle manufacturer.

²Tread depth measurements rounded to nearest whole number.

