

Precise control. Every day.



Precise control in all weather conditions

- ▶ Progressive Sipe Technology: tread design gradually increases the number of sipes in contact with the road as you lean into corners, for excellent traction on wet pavement
- ▶ For medium- to large-displacement scooters

Excellent mileage

- ▶ Progressive tread pattern extends mileage performance

Reliable and reassuring handling and comfort

- ▶ Newly formulated rubber compounds, combined with proven construction



| Size | Load index & Speed rating | Michelin Tube | Overall width | | | | Overall diameter | | | | Max load ¹ | | Tread depth ² | | Preferred rim width (compatible rims) in | |
|-------------------------|---------------------------|-------------------|---------------|--------------|--------------|--------------|------------------|--------------|-----|-------|-----------------------|-----|--------------------------|-------|---|--|
| | | | Static mm | In Use in | Static mm | In Use in | Static mm | In Use in | mm | in | kg | lbs | mm | 32nds | | |
| CITY GRIP™ FRONT | | | | | | | | | | | | | | | | |
| 110/90-12 | 64 P | None avail. or TL | 109 | 4.29 | 118 | 4.65 | 503 | 19.80 | 517 | 20.35 | 280 | 617 | 5 | 6 | 2.50 (2.15 to 3.00) | |
| 120/70-12 | 51 P | TL or 12B1 | 122 | 5.08 | 132 | 5.47 | 473 | 19.17 | 485 | 19.65 | 195 | 430 | 6 | 7 | 3.50 (3.00 to 4.00) | |
| 120/70-12 | 51 S | TL or 12B1 | 122 | 5.08 | 132 | 5.47 | 473 | 19.17 | 485 | 19.65 | 195 | 430 | 6 | 7 | 3.50 (3.00 to 4.00) | |
| 110/90-13 | 56 P | None avail. or TL | 109 | 4.29 | 120 | 4.72 | 528 | 20.79 | 542 | 21.34 | 224 | 494 | 5 | 6 | 2.50 (2.15 to 3.00) | |
| 120/70-14 | 55 P | None avail. or TL | 122 | 4.80 | 134 | 5.28 | 524 | 20.63 | 536 | 21.10 | 218 | 481 | 5 | 6 | 3.50 (3.00 to 4.00) | |
| 120/70-14 | 55 S | None avail. or TL | 122 | 4.80 | 134 | 5.28 | 524 | 20.63 | 536 | 21.10 | 218 | 481 | 5 | 6 | 3.50 (3.00 to 4.00) | |
| 120/70-15 | 56 P | None avail. or TL | 122 | 4.80 | 134 | 5.28 | 549 | 21.61 | 561 | 22.09 | 224 | 494 | 4 | 5 | 3.50 (3.00 to 4.00) | |
| 120/70-15 | 56 S | None avail. or TL | 122 | 4.80 | 134 | 5.28 | 549 | 21.61 | 561 | 22.09 | 224 | 494 | 4 | 5 | 3.50 (3.00 to 4.00) | |
| 110/70-16 | 52 P | None avail. or TL | 110 | 4.33 | 121 | 4.76 | 560 | 22.05 | 570 | 22.44 | 200 | 441 | 4 | 5 | 3.00 | |
| 110/70-16 | 52 S | None avail. or TL | 110 | 4.33 | 121 | 4.76 | 560 | 22.05 | 570 | 22.44 | 200 | 441 | 4 | 5 | 3.00 | |
| 110/80-16 | 55 S | None avail. or TL | 109 | 4.29 | 120 | 4.72 | 582 | 22.91 | 594 | 23.39 | 218 | 481 | 5 | 6 | 2.50 | |
| CITY GRIP™ REAR | | | | | | | | | | | | | | | | |
| 130/70-12 | 56 P | TL or 12B1 | 129 | 5.08 | 139 | 5.47 | 487 | 19.17 | 499 | 19.65 | 224 | 494 | 6 | 7 | 3.50 (3.00 to 4.00) | |
| 130/70-12 Reinf. | 62 P | TL or 12B1 | 129 | 5.08 | 139 | 5.47 | 487 | 19.17 | 499 | 19.65 | 265 | 584 | 6 | 7 | 3.50 (3.00 to 4.00) | |
| 130/70-13 Reinf. | 63 P | None avail. or TL | 129 | 5.08 | 142 | 5.59 | 512 | 20.16 | 524 | 20.63 | 272 | 600 | 6 | 7 | 3.50 (3.00 to 4.00) | |
| 140/60-13 Reinf. | 63 P | None avail. or TL | 139 | 5.47 | 153 | 6.02 | 498 | 19.61 | 510 | 20.08 | 272 | 600 | 6 | 7 | 3.75 (3.00 to 4.00) | |
| 140/60-14 Reinf. | 64 P | None avail. or TL | 139 | 5.47 | 153 | 6.02 | 524 | 20.63 | 536 | 21.10 | 280 | 617 | 6 | 8 | 3.75 (3.00 to 4.00) | |
| 140/60-14 Reinf. | 64 S | None avail. or TL | 139 | 5.47 | 153 | 6.02 | 524 | 20.63 | 536 | 21.10 | 280 | 617 | 6 | 8 | 3.75 (3.00 to 4.00) | |
| 140/70-14 Reinf. | 68 S | None avail. or TL | 139 | 5.47 | 153 | 6.02 | 552 | 21.73 | 566 | 22.28 | 315 | 695 | 6 | 8 | 3.75 (3.00 to 4.00) | |
| 150/70-14 | 66 P | None avail. or TL | 151 | 5.94 | 166 | 6.54 | 566 | 22.28 | 580 | 22.83 | 300 | 662 | 6 | 7 | 4.25 (4.00 to 4.50) | |
| 150/70-14 | 66 S | None avail. or TL | 151 | 5.94 | 166 | 6.54 | 566 | 22.28 | 580 | 22.83 | 300 | 662 | 6 | 7 | 4.25 (4.00 to 4.50) | |
| 130/70-16 | 61 P | None avail. or TL | 129 | 5.08 | 142 | 5.59 | 588 | 23.15 | 600 | 23.62 | 257 | 567 | 6 | 7 | 3.50 (3.00 to 4.00) | |
| 140/70-16 | 65 P | None avail. or TL | 139 | 5.47 | 153 | 6.02 | 602 | 23.70 | 616 | 24.25 | 290 | 639 | 6 | 7 | 3.75 (3.00 to 4.00) | |
| 140/70-16 | 65 S | None avail. or TL | 139 | 5.47 | 153 | 6.02 | 602 | 23.70 | 616 | 24.25 | 290 | 639 | 6 | 7 | 3.75 (3.00 to 4.00) | |

¹Refer to the motorcycle owner's manual for the vehicle's load capacity. Michelin recommends the tire pressures quoted by the vehicle manufacturer.

²Tread depth measurements rounded to nearest whole number.