

MICHELIN STARCROSS MINI MS2 & MH3

MINI MOTOCROSS

World-class performance for minibikes

- ▶ Same knob patterns as full-size MICHELIN® Starcross® MS3 and MH3 tires

Excellent durability

- ▶ Highly resistant to chunking and tearing
- ▶ Reversible knob patterns extend tire life

Choice of knob patterns

- ▶ MS2 knob pattern for soft to intermediate tracks
- ▶ MH3 knob pattern for intermediate to hard tracks



STARCROSS MS2
MINI



STARCROSS MH3
MINI

Size	Load index & Speed rating	Michelin Tube	Overall width		Overall diameter		Max load ¹		Tread depth ²		Preferred rim width (compatible rims) in				
			Static mm	In Use in	Static mm	In Use in	kg	lbs	mm	32nds					
STARCROSS® MINI MS2 FRONT/REAR															
2.50-10	37 J	10MBR	68	2.68	80	3.15	389	15.31	405	15.94	128	282	10	13	1.75
2.75-10	37 J	10MBR	72	2.83	90	3.54	399	15.71	411	16.18	128	282	11	14	1.85
STARCROSS® MINI MS2 FRONT															
2.50-12	30 M	12MCR	68	2.68	85	3.35	440	17.32	449	17.68	106	234	11	14	1.75
60/100-14	30 M	14MBR	60	2.36	65	2.56	476	18.74	490	19.29	106	234	11	14	1.40 (1.50 to 1.85)
70/100-17	40 M	17RSTOP	69	2.72	76	2.99	572	22.52	588	23.15	140	309	11	14	1.60 (1.40 to 1.85)
70/100-19	42 M	19RSTOP	69	2.72	76	2.99	623	24.53	639	25.16	150	331	11	14	1.60 (1.40 to 1.85)
STARCROSS® MINI MS2 REAR															
80/100-12	41 M	12MCR	80	3.15	86	3.39	465	18.31	477	18.78	145	320	14	18	1.85 (1.40 to 1.60)
90/100-14	49 M	14MBR or 14RSTOP	90	3.54	99	3.90	536	21.10	558	21.97	185	408	14	18	2.15 (1.85 to 2.50)
90/100-16	51 M	16RSTOP	90	3.54	99	3.90	586	23.07	600	23.62	195	430	14	18	2.15 (1.85 to 2.50)
STARCROSS® MINI MH3 FRONT/REAR															
2.75-10	37 J	10MBR	72	2.83	90	3.54	399	15.71	411	16.18	128	282	11	14	1.85
STARCROSS® MINI MH3 FRONT															
2.50-12	30 M	12MCR	68	2.68	85	3.35	440	17.32	449	17.68	106	234	11	14	1.75
60/100-14	30 M	14MBR	60	2.36	65	2.56	476	18.74	490	19.29	106	234	11	14	1.40 (1.50 to 1.85)
70/100-17	40 M	17RSTOP	69	2.72	76	2.99	572	22.52	588	23.15	140	309	11	14	1.60 (1.40 to 1.85)
70/100-19	42 M	19RSTOP	69	2.72	76	2.99	623	24.53	639	25.16	150	331	11	14	1.60 (1.40 to 1.85)
STARCROSS® MINI MH3 REAR															
80/100-12	41 M	12MCR	80	3.15	86	3.39	465	18.31	477	18.78	145	320	14	18	1.85 (1.40 to 1.60)
90/100-14	49 M	14MBR or 14RSTOP	90	3.54	99	3.90	536	21.10	558	21.97	185	408	14	18	2.15 (1.85 to 2.50)
90/100-16	51 M	16RSTOP	90	3.54	99	3.90	586	23.07	600	23.62	195	430	14	18	2.15 (1.85 to 2.50)

MICHELIN T63

DUAL SPORT: 50% OFF-ROAD / 50% ROAD

- ▶ True multi-purpose tire: reinforced knobs resist tearing and chunking on asphalt, with excellent traction and stability for off-road use; DOT-legal
- ▶ Knob pattern derived from Dakar-winning MICHELIN® Desert™ tires

Size	Load index & Speed rating	Michelin Tube	Overall width		Overall diameter		Max load ¹		Tread depth ²		Preferred rim width (compatible rims) in				
			Static mm	In Use in	Static mm	In Use in	kg	lbs	mm	32nds					
T63™ FRONT															
80/90-21	48 S	21MDR or 21UHD	80	3.15	88	3.46	677	26.65	695	27.36	180	397	12	15	1.85 (1.60 or 2.15)
90/90-21	54 S	21MDR or 21UHD	90	3.54	99	3.90	695	27.36	713	28.07	212	467	12	15	1.85 (1.60 or 2.15)
T63™ REAR															
130/80-17	65 S	17MH	129	5.08	142	5.59	640	25.20	664	26.14	290	639	17	21	3.00
110/80-18	58 S	18MF	109	4.29	120	4.72	633	24.92	655	25.79	236	520	17	21	2.50 (2.15 or 2.75)
120/80-18	62 S	18MF	119	4.69	131	5.16	649	25.55	671	26.42	265	584	17	21	2.75 (2.50 or 3.00)
130/80-18	66 S	18MFR or 18UHD	129	5.08	142	5.59	665	26.18	689	27.13	300	661	17	21	3.00

¹Refer to the motorcycle owner's manual for the vehicle's load capacity. Michelin recommends the tire pressures quoted by the vehicle manufacturer.

²Tread depth measurements rounded to nearest whole number.

