

Premium-quality replacement tire

Excellent value in a bias-ply replacement tire

- ▶ Outstanding combination of performance and durability at a very attractive price
- ▶ 20% longer tread life than previous generation of MICHELIN® bias-ply touring tires

Grip, longevity and stability

- ▶ Wide tread blocks on the rear tire mean more road-rubber contact
- ▶ Longitudinal and lateral tread grooves for effective water evacuation

Comprehensive range of sizes

- ▶ 25 sizes available to fit a wide range of touring, sport touring and standard bikes



Size	Load index & Speed rating	Michelin Tube	Overall width				Overall diameter				Max load ¹		Tread depth ²		Preferred rim width (compatible rims) in	
			Static mm	In Use in	mm	in	Static mm	In Use in	mm	in	kg	lbs	mm	32nds		
PILOT® ACTIV FRONT																
120/80-16	60 V	TL or 16MI	119	4.69	131	5.16	598	23.54	612	24.09	250	551	4	5	2.75 (2.50 or 3.00)	
110/70-17	54 H	TL or 17MG	110	4.33	121	4.76	586	23.07	596	23.46	212	467	5	6	3.00 (2.75 & 3.50)	
110/80-17	57 H	TL or 17MG	109	4.29	120	4.72	608	23.94	620	24.41	230	507	5	6	2.50 (2.15 to 3.00)	
110/80-17	57 V	TL or 17MG	109	4.29	120	4.72	608	23.94	620	24.41	230	507	5	6	2.50 (2.15 to 3.00)	
120/70-17	58 V	TL or 17MG	122	4.80	134	5.28	600	23.62	612	24.09	236	520	5	6	3.50 (3.00 & 3.75)	
90/90-18	51 H	TL or 18MF	90	3.54	99	3.90	619	24.37	631	24.84	195	430	5	6	2.15 (1.85 or 2.50)	
100/90-18	56 H	TL or 18MF	101	3.98	111	4.37	637	25.08	649	25.55	224	494	5	6	2.50 (2.15 & 2.75)	
100/90-18	56 V	TL or 18MF	101	3.98	111	4.37	637	25.08	649	25.55	224	494	5	6	2.50 (2.15 or 2.75)	
110/80-18	58 V	TL or 18MF	109	4.29	120	4.72	633	24.92	645	25.39	236	520	5	6	2.50 (2.15 to 3.00)	
110/90-18	61 V	TL or 18MF	109	4.29	120	4.72	655	25.79	669	26.34	257	567	5	6	2.50 (2.15 to 3.00)	
100/90-19	57 H	TL or 19MF	101	3.98	111	4.37	663	26.10	675	26.57	230	507	5	6	2.50 (2.15 or 2.75)	
100/90-19	57 V	TL or 19MF	101	3.98	111	4.37	663	26.10	675	26.57	230	507	5	6	2.50 (2.15 or 2.75)	
3.25-19	54 H	TL or 19MF	89	3.50	96	3.78	665	26.18	677	26.65	212	467	5	6	2.15 (1.85 or 2.50)	
PILOT® ACTIV REAR																
130/70-17	62 H	TL or 17MH	129	5.08	142	5.59	614	24.17	626	24.65	265	584	7	9	3.50 (3.00 to 4.00)	
130/80-17	65 H	TL or 17MH	129	5.08	142	5.59	640	25.20	654	25.75	290	639	7	9	3.00 (2.50 to 3.50)	
130/90-17	68 V	TL or 17MI	129	5.08	142	5.59	666	26.22	682	26.85	315	695	7	9	3.00 (2.50 to 3.50)	
140/70-17	66 H	TL or 17MH	139	5.47	153	6.02	628	24.72	642	25.28	300	662	7	9	3.75 (3.50 to 4.00)	
140/80-17	69 V	TL or 17MI	142	5.59	156	6.14	656	25.83	672	26.46	325	717	7	9	3.50 (2.75 to 3.75)	
150/70-17	69 H	TL or 17MI	151	5.94	166	6.54	642	25.28	656	25.83	325	717	7	9	4.25 (3.50 to 4.50)	
150/70-17	69 V	TL or 17MI	151	5.94	166	6.54	642	25.28	656	25.83	325	717	7	9	4.25 (3.50 to 4.50)	
120/90-18	65 H	TL or 18MG	119	4.69	131	5.16	673	26.50	689	27.13	290	639	7	9	2.75 (2.50 or 3.00)	
120/90-18	65 V	TL or 18MG	119	4.69	131	5.16	673	26.50	689	27.13	290	639	7	9	2.75 (2.50 or 3.00)	
130/70-18	63 H	TL or 18MG	129	5.08	142	5.59	639	25.16	651	25.63	272	600	7	9	3.50 (3.00 to 4.00)	
130/80-18	66 V	TL or 18MG	129	5.08	142	5.59	665	26.18	679	26.73	300	662	7	9	3.00 (2.50 to 3.50)	
4.00-18	64 H	TL or 18MG	108	4.25	117	4.61	671	26.42	685	26.97	280	617	7	9	2.50 (2.15 to 3.00)	

¹Refer to the motorcycle owner's manual for the vehicle's load capacity. Michelin recommends the tire pressures quoted by the vehicle manufacturer.

²Tread depth measurements rounded to nearest whole number.