

# MICHELIN PILOT SPORT SC

## SPORTY TIRE FOR MIDSIZE SCOOTERS

### Promotes sport riding for midsized scooters

- ▶ Performance-oriented casing profile for easy maneuverability

### Optimal grip in virtually all conditions

- ▶ Thanks to a semi-slick sport tread design and silica-enriched rubber compound

### Evolved from renowned MICHELIN® Pilot® Sport motorcycle tires

- ▶ Chosen as original equipment for the revolutionary Piaggio MP3

Size	Load index & Speed rating	Michelin Tube	Overall width			Overall diameter			Max load <sup>1</sup>		Tread depth <sup>2</sup>		Preferred rim width (compatible rims) in		
			Static mm	In Use in	In Use mm	Static mm	In Use mm	In Use in	kg	lbs	mm	32nds			
<b>PILOT® SPORT SC FRONT</b>															
110/90-12	64 P	none avail. or TL	109	4.29	118	4.65	503	19.80	517	20.35	280	617	6	7	2.50 (2.15 to 3.00)
120/70-12	51 P	TL or 12B1	122	5.08	132	5.47	473	19.17	485	19.65	195	430	6	7	3.50 (3.00 to 4.00)
110/90-13	56 P	none avail. or TL	109	4.29	120	4.72	528	19.13	542	19.53	224	494	6	7	2.50 (2.15 to 3.00)
120/70-14	55 L	none avail. or TL	122	4.80	134	5.28	524	20.63	536	21.10	218	481	5	6	3.50 (3.00 to 4.00)
120/70-14	55 P	none avail. or TL	122	4.80	134	5.28	524	20.63	536	21.10	218	481	5	6	3.50 (3.00 to 4.00)
120/70-14	55 S	none avail. or TL	122	4.80	134	5.28	524	20.63	536	21.10	218	481	5	6	3.50 (3.00 to 4.00)
120/80-14	58 S	none avail. or TL	119	4.69	131	5.16	548	21.57	562	22.13	236	520	5	6	2.75
<b>PILOT® SPORT SC REAR</b>															
130/70-12	56 P	TL or 12B1	129	5.08	139	5.47	487	19.17	499	19.65	224	494	6	8	3.50 (3.00 to 4.00)
130/70-12	Reinf. 62 P	TL or 12B1	129	5.08	139	5.47	487	19.17	499	19.65	265	584	6	8	3.50 (3.00 to 4.00)
140/70-12	60 P	none avail. or TL	139	5.47	150	5.91	501	19.72	515	20.28	250	551	6	8	4.00 (3.50 to 4.50)
130/60-13	53 P	none avail. or TL	129	5.08	142	5.59	486	19.13	496	19.53	206	454	6	8	3.50 (3.00 to 4.00)
130/70-13	Reinf. 63 P	none avail. or TL	129	5.08	142	5.59	512	20.15	524	20.63	272	600	6	8	3.50 (3.00 to 4.00)
140/60-13	57 L	none avail. or TL	139	5.47	153	6.02	498	19.61	510	20.08	230	507	6	7	3.75 (3.00 to 4.00)
140/60-13	57 P	none avail. or TL	139	5.47	153	6.02	498	19.61	510	20.08	230	507	6	7	3.75 (3.00 to 4.00)
150/70-13	64 S	none avail. or TL	151	5.94	166	6.54	540	21.26	554	21.81	280	617	6	8	4.25 (4.00 to 4.50)
140/70-14	Reinf. 68 S	none avail. or TL	139	5.47	153	6.02	552	21.73	566	22.28	315	694	6	8	3.75 (3.00 to 4.00)
150/70-14	66 S	none avail. or TL	151	5.94	166	6.54	566	22.28	580	22.83	300	662	6	8	4.25 (4.00 to 4.50)



# MICHELIN PILOT SPORT SC RADIAL

## RADIAL FOR TOURING SCOOTERS

### Ideal for large displacement scooters

- ▶ Developed in conjunction with major scooter manufacturers

### High-speed stability and control

- ▶ Radial construction minimizes carcass deformation at high speeds, providing uniform wear, a comfortable ride and exceptional grip

### Precise steering and maneuverability

- ▶ Performance-oriented casing profile and tread design

Size	Load index & Speed rating	Michelin Tube	Overall width			Overall diameter			Max load <sup>1</sup>		Tread depth <sup>2</sup>		Preferred rim width (compatible rims) in		
			Static mm	In Use in	In Use mm	Static mm	In Use mm	In Use in	kg	lbs	mm	32nds			
<b>PILOT® SPORT SC RADIAL FRONT</b>															
120/70R14	55 H	TL	122	4.80	131	5.16	524	20.63	536	21.10	218	481	4	5	3.50
120/70R15	56 H	TL	122	4.80	131	5.16	549	21.61	561	22.09	224	494	4	4	3.50
120/70R16	57 H	TL	125	4.92	134	5.28	574	22.60	586	23.07	230	507	4	4	3.75
<b>PILOT® SPORT SC RADIAL REAR</b>															
160/60R14	65 H	TL	161	6.34	172	6.77	548	21.57	562	22.13	290	639	7	8	4.50
160/60R15	67 H	TL	161	6.34	172	6.77	573	22.56	587	23.11	307	677	7	9	4.50

<sup>1</sup>Refer to the motorcycle owner's manual for the vehicle's load capacity. Michelin recommends the tire pressures quoted by the vehicle manufacturer.

<sup>2</sup>Tread depth measurements rounded to nearest whole number.



SCOOTER