

# MICHELIN *Scorcher* 11

ORIGINAL-EQUIPMENT RADIAL FOR SELECT HARLEY-DAVIDSON® MODELS

- ▶ Original equipment on 2011 Sportster SuperLow®, V-Rod®, V-Rod Muscle® and V-Rod Night Rod® Special motorcycles, with approved fitments for additional model years.
- ▶ Outstanding grip: Semi-slick tread pattern maximizes the contact patch for excellent adhesion on dry roads. Optimized tread groove design efficiently evacuates water for dependable wet grip.
- ▶ Excellent Tread Life: Racing-derived rubber compounds combine durability and high performance.
- ▶ Precise Handling: Michelin radial technology allows for easy maneuverability and impressive agility at highway speeds.
- ▶ Available exclusively at Harley-Davidson® dealers.

Size	Load index & Speed rating	Michelin Tube	Overall width				Overall diameter				Max load <sup>1</sup>		Tread depth <sup>2</sup>		Preferred rim width (compatible rims)
			Static mm	In Use in	Static mm	In Use in	Static mm	In Use in	Static mm	In Use in	kg	lbs	mm	32nds	in
<b>SCORCHER® "11" FRONT</b>															
120/70ZR18 (59 W)	TL	TL	122	4.80	131	5.16	625	24.61	637	25.08	243	536	3	4	3.50 (3.75)
120/70ZR19 (60 W)	TL	TL	122	4.80	131	5.16	651	25.87	663	26.10	250	551	5	6	3.50 (3.75)
<b>SCORCHER® "11" REAR</b>															
150/60ZR17 (66 W)	TL	TL	151	5.95	162	6.38	612	24.09	624	24.57	325	716	6	8	4.25
240/40R18 (79 V)	TL	TL	240	9.44	257	10.12	649	25.55	663	26.10	335	739	6	8	8.50



# MICHELIN *Scorcher* 31

ORIGINAL-EQUIPMENT FOR SELECT HARLEY-DAVIDSON® MODELS

- ▶ Original equipment on 2011 Dyna® Super Glide® Custom, Dyna® Street Bob®, XL 1200 Custom®, Nightster®, 1200 Low, Forty Eight™, Iron 883™ and 883 Roadster™ models, with approved fitments for additional model years.
- ▶ Cruise with confidence: Innovative rubber compounds, incorporating know-how derived from Michelin's decades of road-racing experience, provide remarkable grip on both wet and dry roads.
- ▶ Supple casing design and profile promote rock-solid handling on winding roads.
- ▶ Michelin carbon black-enriched rubber compounds promote excellent durability without compromising performance.
- ▶ Available exclusively at Harley-Davidson® dealers.

Size	Load index & Speed rating	Michelin Tube	Overall width				Overall diameter				Max load <sup>1</sup>		Tread depth <sup>2</sup>		Preferred rim width (compatible rims)
			Static mm	In Use in	Static mm	In Use in	Static mm	In Use in	Static mm	In Use in	kg	lbs	mm	32nds	in
<b>SCORCHER® "31" FRONT</b>															
100/90B19 (57 H)	TL or 19MF	TL or 19MF	101	3.98	111	4.37	663	26.10	675	26.57	230	507	5	6	2.50 (2.15 or 2.75)
<b>SCORCHER® "31" REAR</b>															
160/70B17 (73 V)	TL or 17MI	TL or 17MI	161	6.34	177	6.97	656	25.83	672	26.46	365	805	6	8	4.50

<sup>1</sup>Refer to the motorcycle owner's manual for the vehicle's load capacity. Michelin recommends the tire pressures quoted by the vehicle manufacturer.

<sup>2</sup>Tread depth measurements rounded to nearest whole number.

