

MICHELIN *STARCROSS MS3*

MOTOCROSS: SOFT / INTERMEDIATE

The best traction of all MICHELIN® motocross tires on loose dirt

- ▶ Scoop-like knob design, with widely spaced knobs for mud evacuation
- ▶ Reversible, with equal traction in both directions

Outstanding durability

- ▶ Reinforced knobs resist wear on harder tracks

Size	Load index & Speed rating	Michelin Tube	Overall width		Overall diameter		Max load ¹		Tread depth ²		Preferred rim width (compatible rims) in				
			Static mm	In Use mm	Static mm	In Use mm	kg	lbs	mm	32nds					
STARCROSS® MS3 FRONT															
80/100-21	51 M	21MDR or 21UHD	80	3.15	88	3.46	693	27.28	713	28.07	195	430	12	15	1.85 (1.60 or 2.15)
STARCROSS® MS3 REAR															
100/90-19	57 M	19MFR or 19UHD	101	3.98	111	4.37	663	26.10	683	26.89	230	507	17	21	2.50 (2.15 to 3.00)
110/90-19	62 M	19MER or 19UHD	109	4.29	120	4.72	681	26.81	703	27.68	265	584	17	21	2.50 (2.15 to 3.00)



MICHELIN *STARCROSS MH3*

MOTOCROSS: INTERMEDIATE / HARD

Designed for traction in dry and hard-packed conditions

- ▶ Wide central knobs for forward drive and dependable starts
- ▶ Sculpted side knobs for aggressive cornering
- ▶ Reversible, with massive central knobs that resist chunking

Size	Load index & Speed rating	Michelin Tube	Overall width		Overall diameter		Max load ¹		Tread depth ²		Preferred rim width (compatible rims) in				
			Static mm	In Use mm	Static mm	In Use mm	kg	lbs	mm	32nds					
STARCROSS® MH3 FRONT															
80/100-21	51 M	21MDR or 21UHD	80	3.15	88	3.46	693	27.28	713	28.07	195	430	12	15	1.85 (1.60 or 2.15)
STARCROSS® MH3 REAR															
100/90-19	57 M	19MFR or 19UHD	101	3.98	111	4.37	663	26.10	683	26.89	230	507	17	21	2.50 (2.15 to 3.00)
110/90-19	62 M	19MER or 19UHD	109	4.29	120	4.72	681	26.81	703	27.68	265	584	17	21	2.50 (2.15 to 3.00)



MICHELIN *STARCROSS SAND 4*

MOTOCROSS: REAR TIRE FOR SOFT SAND

Remarkable forward drive on sand tracks

- ▶ Scoop-like knob orientation for exceptional traction in deep sand
- ▶ Ample spacing helps prevent sand from packing in between knobs
- ▶ Recommended for use with MICHELIN® S12 XC™ or Starcross® MS3 front tires

Size	Load index & Speed rating	Michelin Tube	Overall width		Overall diameter		Max load ¹		Tread depth ²		Preferred rim width (compatible rims) in				
			Static mm	In Use mm	Static mm	In Use mm	kg	lbs	mm	32nds					
STARCROSS® SAND 4 REAR															
100/90-19	57 M	19MFR or 19UHD	101	3.98	111	4.37	663	26.10	683	26.97	230	507	17	21	2.50 (2.15 to 3.00)
110/90-19	62 M	19MER or 19UHD	109	4.29	120	4.72	681	26.81	703	27.68	265	584	17	21	2.50 (2.15 to 3.00)

¹Refer to the motorcycle owner's manual for the vehicle's load capacity. Michelin recommends the tire pressures quoted by the vehicle manufacturer.

²Tread depth measurements rounded to nearest whole number.

