

# MICHELIN S12 XC

***MX / OFF-ROAD: SOFT / INTERMEDIATE***

## Most versatile tire in the MICHELIN® off-road range

- ▶ Excels in a wide variety of conditions from soft mud to loose dirt
- ▶ Rigid sidewalls for superb rider feedback
- ▶ Exceptional traction on soft terrain, with tall, narrow knobs for penetration

Size	Load index & Speed rating	Michelin Tube	Overall width				Overall diameter				Max load <sup>1</sup>		Tread depth <sup>2</sup>		Preferred rim width (compatible rims) in
			Static mm	In Use in	Static mm	In Use in	Static mm	In Use in	Static mm	In Use in	kg	lbs	mm	32nds	
<b>S12 XC™ FRONT</b>															
90/90-21 (80/100-21)	21MDR or 21UHD	80	3.15	88	3.46	693	27.28	713	28.07	195	430	12	15	1.85 (1.60 or 2.15)	
<b>S12 XC™ REAR</b>															
120/90-18 (100/100-18)	18MFR, 18UHD	101	3.98	111	4.37	657	25.86	681	26.81	243	536	17	21	2.50 (2.15 or 2.75)	
130/80-18 (110/100-18)	18MFR, 18UHD	109	4.29	120	4.72	677	26.65	703	27.68	280	617	17	21	2.50 (2.15 or 2.75)	
140/80-18 (120/90-18)	18MFR, 18UHD	119	4.69	131	5.16	673	26.50	699	27.52	290	639	17	21	2.75 (2.50 or 3.00)	
120/80-19 (100/90-19)	19MFR or 19UHD	101	3.98	111	4.37	663	26.10	685	26.97	230	507	17	21	2.50 (2.15 to 3.00)	
130/70-19 (110/90-19)	19MER or 19UHD	109	4.29	120	4.72	681	26.81	705	27.76	265	584	17	21	2.50 (2.15 to 3.00)	



# MICHELIN M12 XC

***MX / OFF-ROAD: INTERMEDIATE / HARD***

## Developed for mixed/dry conditions

- ▶ Massive knobs resist tearing on hardpack
- ▶ Knob pattern designed for traction in loose dirt
- ▶ Confidence-inspiring traction and steering

Size	Load index & Speed rating	Michelin Tube	Overall width				Overall diameter				Max load <sup>1</sup>		Tread depth <sup>2</sup>		Preferred rim width (compatible rims) in
			Static mm	In Use in	Static mm	In Use in	Static mm	In Use in	Static mm	In Use in	kg	lbs	mm	32nds	
<b>M12 XC™ FRONT</b>															
90/90-21 (80/100-21)	21MDR or 21UHD	80	3.15	88	3.46	693	27.28	713	28.07	195	430	12	15	1.85 (1.60 or 2.15)	
<b>M12 XC™ REAR</b>															
120/90-18 (100/100-18)	18MFR, 18UHD	101	3.98	111	4.37	657	25.86	681	26.81	243	536	17	21	2.50 (2.15 or 2.75)	
130/80-18 (110/100-18)	18MFR, 18UHD	109	4.29	120	4.72	677	26.65	703	27.68	280	617	17	21	2.50 (2.15 or 2.75)	
120/80-19 (100/90-19)	19MFR or 19UHD	101	3.98	111	4.37	663	26.10	685	26.97	230	507	17	21	2.50 (2.75 or 3.00)	
130/70-19 (110/90-19)	19MER or 19UHD	109	4.29	120	4.72	681	26.81	705	27.76	265	584	17	21	2.50 (2.15 to 3.00)	



OFF-ROAD MX / DUAL SPORT

# MICHELIN CROSS AC10

***DUAL SPORT: 90% OFF-ROAD / 10% ROAD***

- ▶ Excellent traction on varied terrain; especially good on hard-packed trails
- ▶ DOT-legal, with a rubber mixture formulated for long tread life
- ▶ Resists tearing and chunking even under hard use

Size	Load index & Speed rating	Michelin Tube	Overall width				Overall diameter				Max load <sup>1</sup>		Tread depth <sup>2</sup>		Preferred rim width (compatible rims) in
			Static mm	In Use in	Static mm	In Use in	Static mm	In Use in	Static mm	In Use in	kg	lbs	mm	32nds	
<b>CROSS AC10® FRONT</b>															
80/100-21	51 R	21MDR or 21UHD	80	3.15	88	3.46	693	27.28	713	28.07	195	430	12	15	1.85 (1.60 or 2.15)
<b>CROSS AC10® REAR</b>															
100/100-18	59 R	18MFR or 18UHD Med.	101	3.98	111	4.37	657	25.86	681	26.81	243	536	17	21	2.50 (2.15 or 2.75)
110/100-18	64 R	18MFR or 18UHD Med.	109	4.29	120	4.72	677	26.65	703	27.68	280	617	17	21	2.50 (2.15 or 2.75)
120/90-18	65 R	18MFR or 18UHD Med.	119	4.69	131	5.16	673	26.50	699	27.52	290	639	17	21	2.75 (2.50 or 3.00)
100/90-19	57 R	19MFR or 19UHD	101	3.98	111	4.37	663	26.10	685	26.97	230	507	17	21	2.50 (2.15 or 2.75)
110/90-19	62 R	19MER or 19UHD	109	4.29	120	4.72	681	26.81	705	27.76	265	584	17	21	2.50 (2.15 to 3.00)

<sup>1</sup>Refer to the motorcycle owner's manual for the vehicle's load capacity. Michelin recommends the tire pressures quoted by the vehicle manufacturer.

<sup>2</sup>Tread depth measurements rounded to nearest whole number.

